

**Muralo 689 Interior/Exterior Professional Grade Spackle<sup>®</sup>**

<b>Description:</b>	Professional Grade Spackle <sup>®</sup> is the finest quality ready-to-use surfacing compound designed for filling interior and minor exterior surface imperfections in previously painted or primed plaster, wallboard and wood. It has excellent workability, long open time, dries fast, and sands easily to a smooth, paintable surface.		
<b>Recommended Uses:</b>	For interior use in filling holes, cracks, dents and gouges on plaster, wallboard, wood, masonry and painted metal.		
<b>Surface Preparation:</b>	Clean surface to be patched thoroughly. Remove all loose dirt, paint, plaster, wax, grease and dust. Lightly sand glossy surfaces. New or unpainted areas must be primed prior to application with a premium quality acrylic primer.		
<b>Priming:</b>	Prime with premium acrylic primer.		
<b>Application:</b>	Apply with a broad knife (wide or narrow, depending on the size of the area being filled). Spread paste evenly, pressing into holes and cracks, and feathering out the edges. Deep cracks and holes may require more than one application.		
<b>Clean Up:</b>	Soap and water		
<b>Weight/Gal:</b>	14.91 lbs.		
<b>Color:</b>	White		
<b>Viscosity:</b>	Smooth Paste		
<b>Dry Time:</b>	Varies with film thickness, temperature and humidity. Under normal conditions (70°F, 50% RH) Dries in minutes to a hard finish.		
<b>Flash Point:</b>	None (closed cup)		
<b>Solids by Weight:</b>	73.6%		
<b>Packaging:</b>		<b>Per Case</b>	<b>Weight</b>
	Quarts	6	22.36 lbs.
	Gallons	4	60.00 lbs.
<b>Cautions:</b>	Keep out of reach of children. Keep from freezing. Do not apply in temperatures below 45°F. Do not take internally. Close container after each use.		

**DISCLAIMER:** The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

**NOTICE:** Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.

Spackle<sup>®</sup> is a registered trademark of the Muralo Company

Revised 6/3/2005

**The Muralo Company, Inc.**

148 East 5th Street • Bayonne, NJ 07002 • (201) 437-0770 • FAX (201) 437-2316