

Latex Texture Paint**M0300**

Description:	Muralo Latex Texture Paint is a heavy bodied Vinyl Coating with paste-like consistency designed to create three dimensional effects on walls. When spread on the wall or ceiling, it does not sag or flow, but "peaks"; remaining in whatever position it is applied. It can be easily spread, shaped and sculptured to create stunningly distinctive decorative texture effects.
Recommended Uses:	Any paintable interior surface such as plaster, wallboard, wood and masonry. Covers hairline cracks and imperfections to beautify old walls and ceilings. An extra heavy coat of Texture Paint on drywall makes it look more sturdy and obscures the mortar lines on interior block construction better than regular block filler. Do not use over wallpaper. Kalsomine or any other water-soluble material such as glue-size. It should not be used on metals that rust unless they are properly primed.
Surface Preparation:	Surfaces must be clean, dry and free of dirt, grease, soap film and wax. Roughen glossy surfaces with sandpaper or prime with Muralo's Enamel Undercoater #563 for better adhesion. Moisture problems must be dealt with by repairing the source of trouble. Dried water stains should be primed with Muralo 567 Alkyd Primer before painting. Metals that rust should be primed with a good primer such as Muralo's Rust Preventive Primer. Mildew must be removed by scraping or wire-brushing, then washing with a solution of 1-cup bleach and 1-cup Trisodium Phosphate to 2 ½ gallons of water. Allow to soak, then rinse thoroughly.
Application:	Apply with brush, roller or trowel. Use a relatively short length Nylon or Polyester brush of at least 4" width. The paint works easily under the brush, but because of the large amount of coating applied, speed requires a large width brush. A roller cover such as the Elder and Jenks ½" Dual Coater is the best tool of its type for Texture Paint. It works quickly and produces a pleasing stipple. A trowel can also be used to apply the paint to the surface, followed by a pattern-producing tool such as a roller or any improvised method by the applicator such as stiff crumpled paper and straight edge, texture brush. Plastering with texture paint can be attained even by the inexperienced applicator by simply applying the paint with a brush or roller and then, when it is nearly set, smoothing it with a plaster's trowel.
Colors:	White only. Can be tinted before applying, or repainted without priming.
Weight Per Gallon:	13.35 ± 0.2
Hiding:	Texture Paint covers in a single coat
Drying Time:	Overnight. Its thickness makes it slower drying than regular latex paint
Clean Up:	With soap and warm water

Coverage:	60 – 75 sq. ft. per gallon		
Thinning:	Not Recommended		
Formulation:	Pigment = 58.5%		
	Titanium Dioxide Type IV		3.0%
	Silicates		29.0
	Calcium Carbonate		26.5
	Vehicle = 41.5%		
	Poly Vinyl Acetate/Acrylic Resin		4.0%
	Volatile (Water)		<u>37.5</u>
			100.0%
Packaging:		Per Case	Approx. Weight
	1 Gallon	4	54 lbs.
	5 Gallon	Single	60 lbs.
Cautions:	Protect against freezing		
	KEEP OUT OF REACH OF CHILDREN. Do not take internally. Use only with adequate ventilation. Do not apply when temperature is below 50°F.		

DISCLAIMER:

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these Materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women.

Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup.

For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.