

BreatheSafe™

INTERIOR WATER-BASED ZERO VOC PRIMER #2235



For over 110 years, Muralo Paints has engineered innovative products to satisfy the most discriminating customers. Muralo's Breathe Safe™ line is no different. It is virtually odorless and free of VOC's, while still keeping the high performance properties you've come to expect from a Muralo product. Breathe Safe™ Zero VOC Interior Water-based Primer is based on a sustainable chemistry technology, ideal for nursing homes, schools, babies rooms and health care facilities as well as the hotel/motel industries. Breathe Safe™ Interior Primer is formulated with no harmful solvents. It seals unpainted and painted drywall, plaster and wood trim. Specified for space that is occupied during painting. Muralo Breathe Safe™ Interior Primer has been formulated to give excellent hiding and maximum coverage.



Meets or exceeds Green Seal and LEED green building requirements

- Virtually odorless;
- Crystalline silica free;
- High hide;
- Seals porous surfaces;
- Use under flats & enamels;
- Spatter resistance.

The Muralo Company, Inc.

148 East 5th Street • Bayonne, NJ 07002 • Phone: (800) 631-3440 • Fax: (800) 364-8969 • www.muralo.com

Recommend Uses:

Breathe Safe is ideal for nursing homes, schools, babies rooms and health care facilities as well as the hotel/motel industries. Muralo Breathe Safe™ Interior Primer is formulated with no harmful solvents. It seals unpainted and painted drywall, plaster and wood trim. Specified for space that is occupied during painting. Muralo Breathe Safe™ Interior Primer has been formulated to give excellent hiding and maximum coverage.

Surface Preparation:

Breathe Safe™ Interior Primer is formulated as the system primer for all Muralo Breathe™ Safe Zero VOC finishes, however:

1. When finish coating with deep colors, it is recommended that the primer be tinted to the approximate finish coat color;
2. When painting rough and porous concrete block or precast concrete, a premium quality block filler should be applied for optimal finish coat results. Surfaces to be primed must be clean, dry and free of wax, grease, dust, mildew, water-soluble materials and scaling paint. Glossy surfaces must be properly dulled with sandpaper.

Unpainted Surfaces: New plaster or masonry surfaces must be allowed to cure 60 days before priming. Remove loose particles to ensure proper adhesion;

Previously Painted Surfaces: Remove any loose paint and sand to even remaining imperfections;

Unconventional Surfaces: Please consult your Muralo paint dealer for the best specialty primer for difficult surfaces, i.e. bleeding woods, crayon, hard glossy surfaces and metal substrates.

Application:

Breathe Safe™ Interior Primer must be thoroughly mixed before applying. Apply with the recommended roller cover and a synthetic bristle brush. Spray application requires even distribution of the primer. If primer has been unevenly sprayed, feathering off with a brush can be done within 5 minutes of the first spray application. Breathe Safe™ Interior Primer must not be applied when the surface to be painted is less than 50°F.

Finish:

Flat.

Color:

White.

Coverage:

Covers smooth surfaces with similar colors in one coat.

Spreading Rate:

Covers about 500-550 square feet per gallon. Coverage rates vary depending on the porosity of the surface to be painted. Accurate estimating of area to be painted will ensure the most efficient purchasing of the paint. Total the number of square feet you intend to paint.

Dry Time:

Breathe Safe™ Interior Primer will dry to touch in 1/2 hour and can be recoated within 1 hour under normal drying conditions.

Thinning:

Thinning is not necessary, however, if needed, a small amount of water can be added.

Clean-up:

Clean-up with a biodegradable cleaner and water. Use the entire contents of the container or dispose of properly.

Flash Point:

None to boil

Freeze-Thaw:

Keep from freezing

Viscosity:

100 -105 KU

Weight Solids %

50 - 52%

Weight per Gal:

11.72 lbs./gal.

Film Thickness:

3 mil wet

Gloss/Sheen:

3 maximum

V.O.C.(V.O.S):

Contains 0 gms./ltr. or 0 lbs./gal. calculated V.O.C.

Packaging:

Gallons and 5 gallons

Caution:

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves during application or sanding. A dust particle respirator approved by NIOSH/MSHA should be worn when sanding or spraying. Close container after each use. KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING.

First Aid:

If you experience difficulty in breathing, vacate that area to obtain fresh air. IN CASE OF SPILL: Absorb with inert material and dispose of as explained below.

Disposal Information:

Dry, empty containers can be recycled. Small amounts of paint may be dried onto newspapers or rags then disposed of as normal trash. FOLLOW LOCAL COMMUNITY WASTE DISPOSAL GUIDELINES.

Disclaimer:

The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of this material and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

Limited Warranty:

Muralo warrants the performance of this product when applied in complete accordance to label directions and will refund the purchase price or replace this product within one year of date of purchase if defective. Muralo will not be liable for cost of labor or any incidental or consequential damages.