

# Lumber Jacket



## SOLID COLOR ACRYLIC DECKING STAIN ALKYD-MODIFIED #9160

*Muralo Lumber Jacket Solid Color Acrylic Decking Stain is the "Ultimate" in exterior deck stains. It offers maximum color retention, superb adhesion and a water-resistant finish which protects wood from warping and checking. It goes on smoothly and dries to a low sheen finish, with excellent lap sheen uniformity and scuff resistance. It is available in popular wood tone ready-mixed and custom-tinted colors.*



- Rich, low-sheen finish
- Available in White/Bases & 4 Colors
- Scuff resistant
- Fade resistant color
- High hiding

<b>Recommended Uses:</b>	New and old bare or previously stained, properly prepared exterior decks, outdoor furniture and fences. Lumber Jacket Solid Color Acrylic Decking Stain may be used over previously applied, properly prepared oil-based and latex stain.
<b>Surface Preparation:</b>	<b>Proper surface preparation is essential to every satisfactory paint job.</b> The surface to be stained must be clean, firm, completely dry, and free from all dirt, dust, grease, oil and wax. Certain types of wood can develop mill glaze; a hard, shiny coating that results from processing the wood. If your new surface exhibits this look and shininess, hand sanding or chemical cleaning may be required to remove it. Please consult your Muralo dealer for the proper procedure. Muralo Lumber Jacket Solid Color Acrylic Decking Stain is not recommended for use over surfaces previously coated with silicone based paints or stains unless they have weathered for a period of 2 years. If you are not sure about the type of coating previously used, it is best to apply over a small area to test for proper adhesion.
<b>Application:</b>	Stir the paint thoroughly. If using more than one can of a color mix together to insure uniformity. Lumber Jacket 100% Acrylic Solid Color Stain may be applied by brush, roller or spray. Use high quality brushes and rollers. For best results: <b>Brush:</b> A good quality synthetic or nylon bristle brush <b>Roller:</b> May be applied with all rollers; long nap rollers are recommended for rough surfaces and production work. <b>Spray:</b> May be applied with airless or conventional spray equipment. Tip sizes and atomization pressures will vary with the type of equipment used. Usually an 8 to 12 inch fan at 1 foot is ideal for airless and can be obtained with a tip size from .015" to .018". For conventional spraying, usually 0.02" to .01" nozzle with air cap to give a 4 to 12" fan at a distance of 1 foot, gives excellent results. Follow spray equipment manufacturers recommendations.
<b>Special Priming Instructions:</b>	Generally, priming under Lumber Jacket Solid Color Stain is not required. However, if the wood to be stained is new and prone to tannin stain release, prime with one coat of Muralo Lumber Jacket Oil Based Primer 9400 before applying Lumber Jacket Stain. Priming is particularly important if the desired stain color is white or a light pastel shade.
<b>Colors:</b>	White, 4 premixed colors and 4 tint bases
<b>Package Sizes:</b>	Gallons
<b>Coverage:</b>	400 sq. ft. per gallon on average. More porous surfaces result in lower coverage per gallon
<b>Dry Time:</b>	Dries approximately in one hour under normal conditions. High humidity and low temperatures will prolong dry time. Can be recoated in 4 hours
<b>V.O.C.:</b>	Contains max. 200 gms./ltr. Or 1.67 gal./lb.
<b>Weight Per Gal:</b>	10-11 lbs. per gallon
<b>Viscosity:</b>	68 - 72 KU
<b>Flash Point:</b>	None water based stain
<b>Features &amp; Benefits:</b>	<ul style="list-style-type: none"> <li>• Proprietary 100% Acrylic Resin System</li> <li>• Outlasts the Competition</li> <li>• Unique Low-Sheen Finish</li> <li>• Withstands weather better and minimizes lapping</li> <li>• Reduces the need for custom tinting</li> <li>• Latex Based Formula</li> <li>• Soap and water clean-up</li> <li>• Fast Drying</li> </ul>
<b>Thinning:</b>	Thinning is not necessary, but can be reduced by adding up to 1/2 pint of water per gallon in hot weather conditions.
<b>Clean Up:</b>	<b>Use Completely or Dispose of Properly.</b> Save unused product for touch up purposes or household hazardous waste collection program. Dry, empty containers may be recycled in a can recycling program. <b>Local disposal requirements vary; consult your sanitation department or state-designated environmental agency for information on disposal.</b>
<b>Caution:</b>	KEEP OUT OF REACH OF CHILDREN. Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. Do not take internally. Keep from freezing. Do not apply when temperature is below 50° F. Contains: Crystalline Silica which may cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. Use only with adequate ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.
<b>First Aid:</b>	If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.
<b>Disclaimer:</b>	The information contained herein is presented in good faith. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must take independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations. <b>NOTICE:</b> Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For additional information, contact the USEPA/Lead information Hotline at 1-800-LEAD-FYI.